

Solvent Extraction



Petroleum residue is the heavy fraction left after crude distillation. De-Asphalted Oil (DAO) will be produced during all kinds of solvent extraction. These oils are the feedstock for downstream FCC units and hydrocracking units.

Depending on the system configuration, level monitoring of the separator, pre-flash, stripping tower and hot oil phase may be included in the buffer tank, flash tank, separator and stripping tower.

Challenges

Level control is critical for the Solvent Extraction. The extreme conditions of application include high temperature, high pressure and the presence of steam, etc.

Products

- TRG802X Guided Wave Radar Level Transmitter

The latest generation of TRG802X series guided wave radar level transmitter is a two-wire 24VDC powered level transmitter, which adopts advanced microprocessor and unique echo processing technology.

TRG802X series guided wave radar level transmitter can be applied to various complex working conditions and applications. Whether it is a light hydrocarbon or water-based solution, it is suitable.

Features

1. Multi-variable 2-wire system and 24VDC loop-powered level transmitter can be used to measure level, interface, volume or flow.
2. The level measurement results are not affected by the change of medium properties.
3. It is no need to calibrate by adjusting the actual level.
4. Select the probe with function of "anti-overflow ", the true level to the process connection seal can be measured directly without special algorithm.
5. 4 buttons and graphical LCD display can easily observe the instrument configuration information and signal waveform diagram.
6. Use split structure, the electronic device can be replaced without opening the storage tank.

● **UHC Magnetic Level Gauge**

HC magnetic level gauge provides a safer, more reliable and more visible option than conventional glass level gauge. The float moves up and down with the change of level, and the float transmits the level signal through the coupling magnetic field, which divides into the local indication type and the remote transmission output type.

Chamber and float have a variety of materials and pressure-grade options and are suitable for complex process applications of current major operating devices.

Features

1. The float adopts 304,316 L, TA2 and TC4 material. It has good temperature resistance and can reach to 450°C.
2. The welding process meets the requirements of PED welding process. The chamber is made of 304,316 L. The maximum pressure can reach to 26 MPa.
3. Local indicator type and remote output type with level alarm are optional.
4. According to customer requirements, through a variety of production types, the products can be applied to a variety of working conditions.